

AUTOMATIC WATER FILTRATION SYSTEMS

DEAN BENNETT SUPPLY Ph 800-621-4291

1/9/2012



**SO7AF1016 Bottled Water Factory for Rural Well Water – Whole House
Automatic Taste & Odor Filter \$ 845.00 + \$ 70.00 S&H**

Same whole house improvement to your water supply if using rural well water. Unit comes with by-pass valve and #5600 control valve assembly to make your taste and odor treatment of well water fully automatic. Both the service flow rate and backwash rate are a maximum of 5 gpm.



**SO7UF06C Deluxe Undercounter Activated Carbon Taste & Odor Filter
\$ 220.00 + \$ 20.00 S&H**

Simple to install and easily replaces small standard cartridge type filters. Mineral is easily replaceable approximately every three years. Compact in size (7" wide x 20" high) so it will fit under most kitchen sinks. Service flow rate is 3 gpm. Like having bottled water from your kitchen tap.



DWS2M

**DWS2MKIT 2-Stage Taste / Odor / Chemical / Heavy Metals / & Giardia
Removal System w/ Auto Shut-off Valve \$ 145.00 + \$ 10.00 S&H**

Shipped to you pre-assembled and ready for easy installation. Comes complete with both filter cartridges. Stage #1 has a PFC1 dual purpose carbon impregnated cellulose cartridge polishing your water and trapping sediment down to 5 micron. Stage #2 has a PFCBR210 carbon block multimedia cartridge that greatly reduces the amounts of heavy metals and VOCs in your water. The cartridge will remove up to 96% of lead and upto 98% of mercury. In addition this cartridge will remove up to 99% of giardia and cryptosporidium cysts as well as sediment particles down to 1/2 micron in size. To insure that your water is always being filtered this unit comes with a WQA validated, 1800 gallon, patented automatic shut-off valve made from NSF listed materials. Filter has a lead free, long reach chrome faucet that meets State of California requirements. Unit has a white aluminum mounting bracket with stainless steel screws. A saddle valve for tapping into your water service line is also included.



**S11TS32DR6 Tannin / Hardness / Iron Removal System w/Digital Demand
Regeneration Control Valve \$ 1830.00 + \$ 80.00 S&H**

The removal of organic tannins cannot be accomplished with a standard water softener or filter. Tannins usually give your water a yellow or brownish cast that does not settle out and is very difficult to remove even with oxidation and filtration. Tannins can be removed by F&W's ion exchange system. In addition to removal of organic tannins, this system reduces hardness and clear water iron with the use of premium grade multiple resins. Be sure to use salt containing iron control agents or use packaged iron control products (ie Iron Out) if iron is present to keep your mineral bed in top condition.

Maximum Hardness Removal	100 gpg	Maximum Clear Iron Removal	4 ppm
Maximum Tannin Removal	4 gpg	Maximum Service Flow Rate	5 gpm