

# TANK FLOATS & VALVES

11 - 9 - 11

DEAN BENNETT SUPPLY CO  
Toll Free : 800-621-4291  
PRICES ARE YOUR NET COSTS  
Page 66c

## ALUMINUM STOCK TANK FLOATS



The aluminum stock tank float will operate both high and low pressure cut-off valves for many years without losing its buoyancy. The welded aluminum stock tank float can withstand sub freezing winter conditions, the scorching temperatures of summer, and the physical abuse caused by livestock. The aluminum stock tank float is made of corrosion resistant welded aluminum

| Price @  | Description                                |
|----------|--|
| \$ 56.25 | 12" Flat Aluminum Stock Tank Float 12ASTF  |
| \$ 45.75 | 8" Flat Aluminum Stock Tank Float 8ASTF    |
| \$ 27.95 | 10" Molded Plastic Stock Tank Float 10PSTF |



8-1/2" long Brass Pigtail Tie Rod goes through the flat Reliable stock tank float and is adjustable with the bronze clamp. This type pigtail can be used with any type of float valve, whether it has a short arm like the Robert Bob Float, or a long arm like the Midland or AY McDonald stock tank float valves.

|          |         |   |
|----------|---------|---|
| \$ 8.25  | 812RROD | 8-1/2" Brass Pigtail Rod with Bronze Adjustment Clamp |
| \$ 16.50 | 15RROD  | 15" Brass Pigtail Rod with Aluminum Adjustment Clamp  |



1/4" Brass Rod is 12-1/2" long with 1/4"-20 thread on one end and an eye on the other end. These can be used with Robert Bob Floats to use the reliable stock tank float.

|         |          |   |
|---------|----------|---|
| \$ 7.70 | 1212RROD | 12-1/2" long Brass Rod with 1/4"-20 thread x flat eye ends. |
|---------|----------|---|



## AY McDONALD FLOAT VALVES

\$ 35.75 #8713 1" AY McDONALD Float Valve has a brass valve body that houses a rubber ball. The float arm is made of cast iron and is 19" long with a hole in the end for mounting your flat tank float.



## HARD RUBBER FLAT FLOATS

These Hard rubber flat floats are used with any of the above float valves to control the water level in your stock tank. Rubber float measures 2-3/4" thick, 12" diameter, and has a 3/8" hole in the center for mounting to the float valve. The durability of hard rubber floats make them attractive for use where livestock are rough on the tank float.

|          |       |  |
|----------|-------|--|
| \$ 28.50 | #8715 | Flat Hard Rubber Float for use with long arm float valves. |
|----------|-------|--|



THESE FLOATS CAN BE COMBINED WITH OTHER ITEMS IN OUR CATALOG TO QUALIFY FOR OUR \$ 1,000.00 FULL FREIGHT PREPAID ORDER POLICY